

# **Specification**

### **Key Features**

Intel® high-performance workstation W680 chipset, supports Intel 12th/13th and 14th generation processors. UDIMM memory slots, supports up to 128G memory, memory read and write speed. 1 standard PCIe 5.0 x16 (x16 slot), 2 standard PCIe 4.0 x4 (x8 slot) Slot), 1 standard PCIe 3.0 x4 (x4 slot) for flexible expansion. 8 hard disks, storage type supports 6G SATAIII, providing a variety of storage for enterprise applications Solution. 2.5G network interfaces and 1 network management interface, providing a variety of Network transmission and communication solutions remote monitoring of host power, voltage, temperature, fan and other hardware Working status. 500W or CRPS 550W/800/1300W 2.0, lockable chassis with intrusion detection, self encrypting drives



### **Tech Specs**

System Master:	CPU:- ADL-S platform Intel 12th/13th & 14th generation Core processor  Bridge piece:- Intel® W680 Chipset
Graphics:	Chip:- ASPEED AST2600 BMC Interface:- 1 x VGA,1 x DP,1 x HDMI
Memory	Type:- 4 UDIMM memory slots; support up to DDR5 4800/5600MT/s

#### INP TECHNOLOGIES PVT. LTD.

## i5000WH



	Memory capacity:- Support up to 128GB
	Memory size:- 8GB,16GB, 32GB
Network	Controller:- Intel i226 Enterprise Network Controller
	2.5G Network:- 2 x RJ-45 2.5GbE LAN ports, support 10/100/1000/2500Mbps
	IPMI management interface:- 1 standard RJ45, 10/100/1000Mbps network interface
Storage	Sata:- 8 SATA3 6Gb/s ports, support Raid 0, 1, 5, 10
	M.2 :- 1 M.2 2242/2280 interface, support PCI-E 4.0 x4; 1 M.2 2280 interface, support PCIE3.0 x 4
Expansion Slots	-1 standard PCle 5.0 x16 (x16 slot), 2 standard PCle 4.0 x4 (x8 slot)
	-1 standard PCle 3.0 x4 (x4 slot)
Backplane I/O interface	-1 x IPMI management port, 5 x USB 3.0 ports, 2 x RJ-45 2.5GbE LAN ports, 1 x type-C port
	-1 x COM port, 1 x UID switch (with LED light), 1 x audio port, 1 x VGA port, 1 x HDMI port, 1 x DP port
I/O Interface	-1 x front COM port pin, 5 x 4-pin fan connectors, 1 x chassis opening detection connector, 1 x Audio pin (connected to the front panel)
	- 1 x 24-pin power connector + 8-pin power connector + 8-pin reserved power connector
	- 1 x USB 3.0 pin header, supports up to 2 devices; 1 x USB 2.0

#### INP TECHNOLOGIES PVT. LTD.

## i5000WH



	pin header, supports up to two devices, 1 M.2 2242/2280 interface, supports PCI-E 4.0 x4; 1 M.2 2280 interface, supports PCIE3.0 x 4; 1 x USB3.0 Type A; 2 x GPIO headers
Operating system	Windows Enterprise 64 Bit / Linux
Configuration Services	<ul><li>Factory Pre loaded Operating System</li><li>BIOS customization</li><li>Hardware customization</li></ul>
Temperature and humidity requirements	<ul> <li>Working humidity requirement:- 8%~90% without condensation</li> <li>Storage temperature:40~70 degrees Celsius</li> <li>Non-operating humidity requirement:- 5%~95% without condensation</li> </ul>
Keyboard & Mouse	USB keyboard and Optical Mouse
Warranty	3 to 5 year Limited warranty